

MINOMAT Series

Sophisticated design with compact body size and low noise operation.

The concept of this machine is General Operation. The combination of function and efficiency created a new design which comes even closer to human character. The functions and designing characteristics such as color variation of MINOMAT 55&65 Series help to create a comfortable environment in the work shop.



FEATURES

- Decreased operation sound (7dB compare to previous series)
- Smaller occupation than previous series. (30% in case of 65 type)
- Fashionable design together with color variation.
- Decreased down time thanks to the air cylinder locking device.
- Inverter controlled induction motor squeegee carriage at constant speed and variable speed.
- Pneumatic change over and pressure control of squeegee carriage.
- Simple control of squeegee stroke by magnet switch.
- Emergency stop fixed on the frame holder to provide sensitive movement at any time.
- Double table system facilities easy registration.
- Stainless steel table for the durability and long life.

SPECIFICATION

	5575	6590	80120	100120
Max printing area	550x750	650x900	800x1200	1000x1200
Max. printing frame	900x1050	1000x1200	1150x1500	1350x1500
Thickness of substrate (mm)	0-50			
Peel off speed (mm)	0-25			
Max. machine speed (cycle/sec)	1000		800	700
SQG carriage speed (mm/sec)	100-900			
Fine registration (mm)	±10			
Printing table height (mm)	900		980	
Machine dimension (mm)	850x1420x1355	1000x1520x1355	1300x1670x1455	1300x2010x1455
Machine weight (kg)	490	540	620	680
Electric consumption	200V 3ph. 1.5kw 15A			
Compressed air consumption (l/min)	15			

All the specification and parts are subjective to change without prior notice.

COLOR VARIATION



MINO INTERNATIONAL LTD.

4-47-54 NUKUI, NERIMA-KU, TOKYO

TEL:+81-(0)3-3577-1621

FAX:+81-(0)3-3577-3326

WEB:<http://www.mino.co.jp>